



NetClock® WiSync™ Options and Accessories

Digital Elapsed Timer Model NWT



Model NWT is a digital display clock that synchronizes to a NetClock® master clock through the 900 MHz transmitter. The NWT also functions as an elapsed timer in conjunction with a control box (purchased separately). Signal repeater included. The red LED hour and minute display is programmable for 12- or 24-hour formats.

- 2.5" 24V Elapsed Timer, 4-digit, Model NWT-D25R4P-024
- 2.5" 110V Elapsed Timer, 4-digit, Model NWT-D25R4P-110
- 2.5" 24V Elapsed Timer, 6-digit, Model NWT-D25R6P-024
- 2.5" 110V Elapsed Timer, 6-digit, Model NWT-D25R6P-110
- 4.0" 24V Elapsed Timer, 4-digit, Model NWT-D40R4P-024
- 4.0" 110V Elapsed Timer, 4-digit, Model NWT-D40R4P-110
- 4.0" 24V Elapsed Timer, 6-digit, Model NWT-D40R6P-024
- 4.0" 110V Elapsed Timer, 6-digit, Model NWT-D40R6P-110

Elapsed Timer Control Box Model NWT-ETCB



Model NWT-ETCB controls the timer functions of a digital elapsed-time clock. The chronograph functions of the digital clock count up in Hour:Minute (HH:MM) mode or Minute:Second (MM:SS) mode. An included countdown mode can be displayed in either HH:MM or MM:SS format. Both count up and down can be interrupted and either resumed or reset. Digital clock display time is configurable as either hours and minutes or minutes and seconds. The unit features standard double gang box mounting.

Digital Double Mount Model MDDP-XXY



Model MDDP provides a double mount for two digital clocks (purchased separately).

- XX = size of clock (2.5" = 25 or 4.0" = 40)
- Y = number of digits (4 or 6)

Metal Base Dimensions: 5.35" L x 6.20" W x 0.55" D
 Mounting Base Dimensions: 5.75" L x 5.53" W x 0.75" D
 Pole Dimensions: 12.72" L x 2.32" W x 0.79" D

Example:
 MDDP-256 = Double Mount for 2.5", 6 digit digital clock